ALL TYPES OF FRAMES

CERTIFICATES

→ **Certified for internal application**
1. Certificate of Constancy of Performance 1322-CPR-52206003 (IBS Austria) referring to European Technical Assessment ETA-22/0324
2. Certificate of Constancy of Performance AC 158-UWB_W1154 referring to National Technical Assessment KOT-2017/0156 rev. 4

→ **Certified for external application**
Certificate of Constancy of Performance 2268-CPR-478 (KIWA)

Complemented with relevant Declaration of Performance

→ **Certified also by:**
Efectis France, Efectis Nederland, Kiwa Inspecta UAB in Lithuania

DOOR MANUFACTURED TO CUSTOMER ORDER

STANDARD

- door leaf constructed of 2 steel skins 0.75 mm, edge rebated 18 x 18 mm total thickness 65 mm; reinforced for door closer application on both sides
- corner type door frame of extruded aluminum, 2.5-3.0 mm; fitted with perimeter rubber gasket and intumescent fire gasket
- door leaf inlet composed of rockwool; weight of door 30 kg/m^2
- finish: PPC, palette RAL (258 colours, except signal ones)
- 2 pcs of hinges, non-regulated, stainless steel
- DIN-standard lock, PZ 72 mm, backset 65 mm
- stainless steel lever handle-handle set, U-form, on long shield
- PZ cylinder, 3 keys
- 2 pcs of safety pins (in case of 3 hinges – 1 pc of safety pin)
- flush bolt in astragal of passive leaf (double leaf door)
- temporary-affixed steel bar threshold – for transportation only

ALTERNATIVE EQUIPMENT

- door frame: block, embracing (optionally with thermal break) or other type
- hinges regulated 3D (up/down, left/right, depth)

ADDITIONAL EQUIPMENT

- multipoint locks, panic locks, solenoid and motor
- ironmongery: knobs, panic bars, pull bars
- electric strike plates, magnet locks, magnet contacts
- glass vision panel, rectangular or round, single or double glass
- fire rated ventilation grill
- smoke resistant gasket (S_{a4}, S_{200})
- automatic dropping gasket
- rain drip cap on door frame and/or on lower part of door leaf
- door closers
- alternative equipment and other door features on request

TECHNICAL PARAMETERS

- basic features
  - mechanical resistance: class 3 (optional up to 4) according to standard EN 1192
  - mechanical durability: class 5 according to standard EN 16034 (200 000 cycles)
  - corrosion class: C3 (optional C5) according to standard EN ISO 12944
  - ability to release: confirmed
- optional: other classifications
- other functional features – according to relevant Declaration of Performance

CORNER AND EMBRACING FRAME

→ front view and cross section



range of equipment and necessary wall treatment (cut-outs) **are shown on separate data sheets**



→ detail C



→ detail D



→ **calculation of wall opening versus clear opening is the same for corner and embracing door frames:**



→ corner aluminium frame



→ embracing aluminium frame



→ corner aluminium frame with thermal break



→ embracing aluminium frame with thermal break

NOTE! door frame and installation gap to be duly filled, in accordance with certificate

→ **heat transfer coefficient Ud [W/m²K]**

corner frame	**without** thermal break	0,92
	with thermal break	0,92
wall embracing frame	**without** thermal break	1,2
	with thermal break	1,1

- automatic dropping gasket obligatory
- ventilation grill non applicable for doors with declared thermal insulation coefficient
- U value not calculated for doors equipped with glass vision panel

→ **acoustic insulation coefficient**

acoustic insulation Rw (C; Ctr)	
door without glass vision panel	37 (-2; -7)
door with glass vision panel	35 (-2; -4)

- automatic dropping gasket obligatory for acoustic doors
- ventilation grill non applicable for acoustic doors
- glazing type and dimensions according to the relevant DoP

CORNER AND EMBRACING FRAME

→ front view and cross section





→ detail C



→ detail D



range of equipment and necessary wall treatment (cut-outs) **are shown on separate data sheets**

→ **calculation of wall opening versus clear opening is the same for corner and embracing door frames:**



→ corner aluminium frame



→ embracing aluminium frame



→ corner aluminium frame with thermal break



→ embracing aluminium frame with thermal break

NOTE! door frame and installation gap to be duly filled, in accordance with certificate

→ **heat transfer coefficient Ud [W/m²K]**

corner frame	**without** thermal break	1,1
	with thermal break	1,1
wall embracing frame	**without** thermal break	1,2
	with thermal break	1,2

- automatic dropping gasket obligatory
- ventilation grill non applicable for doors with declared thermal insulation coefficient
- U value not calculated for doors equipped with glass vision panel

→ **acoustic insulation coefficient**

acoustic insulation Rw (C; Ctr)	
door without glass vision panel	36 (-1; -3)
door with glass vision panel	n.p.d.

- automatic dropping gasket obligatory for acoustic doors
- ventilation grill non applicable for acoustic doors
- glazing type and dimensions according to the relevant DoP

BLOCK FRAME

→ front view and cross section



range of equipment and necessary wall treatment (cut-outs) **are shown on separate data sheets**



→ detail C



→ detail D



→ **calculation of wall opening versus clear opening is the same for the block frames:**



→ block aluminium frame



→ block aluminium frame with thermal break

NOTE! door frame and installation gap to be duly filled, in accordance with certificate

→ **heat transfer coefficient Ud [W/m²K]**

block frame	**without** thermal break	1,6
	with thermal break	1,3

- automatic dropping gasket and frame filled with plaster board or mortar obligatory
- ventilation grill non applicable for doors with declared thermal insulation coefficient
- U value not calculated for doors equipped with glass vision panel

→ **acoustic insulation coefficient**

acoustic insulation Rw (C; Ctr)	
door without glass vision panel	37 (-2; -7)
door with glass vision panel	35 (-2; -4)

- automatic dropping gasket obligatory for acoustic doors
- ventilation grill non applicable for acoustic doors
- glazing type and dimensions according to the relevant DoP

BLOCK FRAME

→ front view and cross section



range of equipment and necessary wall treatment (cut-outs) **are shown on separate data sheets**



→ detail C



→ detail D



→ **calculation of wall opening versus clear opening is the same for the block frames:**



→ block aluminium frame



→ block aluminium frame with thermal break

NOTE! door frame and installation gap to be duly filled, in accordance with certificate

→ **heat transfer coefficient Ud [W/m²K]**

block frame	**without** thermal break	1,4
	with thermal break	1,3

- automatic dropping gasket and frame filled with plaster board or mortar obligatory
- ventilation grill non applicable for doors with declared thermal insulation coefficient
- U value not calculated for doors equipped with glass vision panel

→ **acoustic insulation coefficient**

acoustic insulation Rw (C; Ctr)	
door without glass vision panel	36 (-1; -3)
door with glass vision panel	n.p.d.

- automatic dropping gasket obligatory for acoustic doors
- ventilation grill non applicable for acoustic doors
- glazing type and dimensions according to the relevant DoP

HYBRID FRAME 60N AND 60NM1

→ front view and cross section



range of equipment and necessary wall treatment (cut-outs) **are shown on separate data sheets**



→ detail C



→ detail D



→ **calculation of wall opening versus clear opening for the hybrid door frames:**



→ hybrid aluminium frame 60N



→ hybrid aluminium frame 60NM1

NOTE! door frame and installation gap to be duly filled, in accordance with certificate

→ **heat transfer coefficient Ud [W/m²K]**

hybrid frame	**without** thermal break	1,2

- automatic dropping gasket obligatory
- ventilation grill non applicable for doors with declared thermal insulation coefficient
- U value not calculated for doors equipped with glass vision panel

→ **acoustic insulation coefficient**

acoustic insulation Rw (C; Ctr)	
door without glass vision panel	37 (-2; -7)
door with glass vision panel	35 (-2; -4)

- automatic dropping gasket obligatory for acoustic doors
- ventilation grill non applicable for acoustic doors
- glazing type and dimensions according to the relevant DoP

HYBRID FRAME 60N AND 60NM1

→ front view and cross section



range of equipment and necessary wall treatment (cut-outs) **are shown on separate data sheets**



→ detail C



→ detail D



→ **calculation of wall opening versus clear opening for the hybrid door frames:**



→ hybrid aluminium frame 60N



→ hybrid aluminium frame 60NM1

NOTE! door frame and installation gap to be duly filled, in accordance with certificate

→ **heat transfer coefficient Ud [W/m²K]**

hybrid frame	**without** thermal break	1,3

- automatic dropping gasket obligatory
- ventilation grill non applicable for doors with declared thermal insulation coefficient
- U value not calculated for doors equipped with glass vision panel

→ **acoustic insulation coefficient**

acoustic insulation Rw (C; Ctr)	
door without glass vision panel	36 (-1; -3)
door with glass vision panel	n.p.d.

- automatic dropping gasket obligatory for acoustic doors
- ventilation grill non applicable for acoustic doors
- glazing type and dimensions according to the relevant DoP

CORNER AND EMBRACING FRAME with hidden rebate (HP)

→ front view and cross section



range of equipment and necessary wall treatment (cut-outs) **are shown on separate data sheets**



→ detail C



→ detail D



→ **calculation of wall opening versus clear opening is the same for the corner and embracing frames:**



→ corner aluminium frame for doors with hidden rebate



→ embracing aluminium frame for doors with hidden rebate

NOTE! door frame and installation gap to be duly filled, in accordance with certificate

→ **heat transfer coefficient Ud [W/m²K]**

corner HP frame	**without** thermal break	0,92
wall embracing HP frame	**without** thermal break	1,2

- automatic dropping gasket obligatory
- ventilation grill non applicable for doors with declared thermal insulation coefficient
- U value not calculated for doors equipped with glass vision panel

→ **acoustic insulation coefficient**

acoustic insulation Rw (C; Ctr)	
door without glass vision panel	37 (-2; -7)
door with glass vision panel	35 (-2; -4)

- automatic dropping gasket obligatory for acoustic doors
- ventilation grill non applicable for acoustic doors
- glazing type and dimensions according to the relevant DoP

CORNER AND EMBRACING FRAME with hidden rebate (HP)

→ front view and cross section



range of equipment and necessary wall treatment (cut-outs) **are shown on separate data sheets**



→ detail C



→ detail D



→ **calculation of wall opening versus clear opening is the same for the corner and embracing frames:**



→ corner aluminium frame for doors with hidden rebate



→ embracing aluminium frame for doors with hidden rebate

NOTE! door frame and installation gap to be duly filled, in accordance with certificate

→ **heat transfer coefficient Ud [W/m²K]**

corner HP frame	**without** thermal break	1,1
wall embracing HP frame	**without** thermal break	1,2

- automatic dropping gasket obligatory
- ventilation grill non applicable for doors with declared thermal insulation coefficient
- U value not calculated for doors equipped with glass vision panel

→ **acoustic insulation coefficient**

acoustic insulation Rw (C; Ctr)	
door without glass vision panel	36 (-1; -3)
door with glass vision panel	n.p.d.

- automatic dropping gasket obligatory for acoustic doors
- ventilation grill non applicable for acoustic doors
- glazing type and dimensions according to the relevant DoP

DFM DOORS

BLOCK FRAME with hidden rebate (HP)

→ front view and cross section



range of equipment and necessary wall treatment (cut-outs) **are shown on separate data sheets**



→ detail C



→ detail D



→ **calculation of wall opening versus clear opening for the block frames with hidden rebate:**



→ block aluminium frame
for doors with hidden rebate

NOTE! door frame and installation gap to be duly filled, in accordance with certificate

→ **heat transfer coefficient Ud [W/m²K]**

block HP frame	**without** thermal break	1,6

- automatic dropping gasket and frame filled with plaster board or mortar obligatory
- ventilation grill non applicable for doors with declared thermal insulation coefficient
- U value not calculated for doors equipped with glass vision panel

→ **acoustic insulation coefficient**

acoustic insulation Rw (C; Ctr)	
door without glass vision panel	37 (-2; -7)
door with glass vision panel	35 (-2; -4)

- automatic dropping gasket obligatory for acoustic doors
- ventilation grill non applicable for acoustic doors
- glazing type and dimensions according to the relevant DoP

BLOCK FRAME with hidden rebate (HP)

→ front view and cross section





→ detail C



→ detail D



range of equipment and necessary wall treatment (cut-outs) **are shown on separate data sheets**

→ **calculation of wall opening versus clear opening for the block frames with hidden rebate:**



→ block aluminium frame for doors with hidden rebate

NOTE! door frame and installation gap to be duly filled, in accordance with certificate

→ **heat transfer coefficient Ud [W/m²K]**

block HP frame	**without** thermal break	1,4

- automatic dropping gasket and frame filled with plaster board or mortar obligatory
- ventilation grill non applicable for doors with declared thermal insulation coefficient
- U value not calculated for doors equipped with glass vision panel

→ **acoustic insulation coefficient**

acoustic insulation Rw (C; Ctr)	
door without glass vision panel	36 (-1; -3)
door with glass vision panel	n.p.d.

- automatic dropping gasket obligatory for acoustic doors
- ventilation grill non applicable for acoustic doors
- glazing type and dimensions according to the relevant DoP