DFM DOORS

ALL TYPES OF FRAMES

CERTIFICATES

→ **Certified for internal application**
Certificate of Constancy of Performance
1322-CPR-52206003 (IBS Austria) referring
to European Technical Assessment ETA-22/0324

→ **Certified for external application**
Certificate of Constancy of Performance
2268-CPR-481 (KIWA)

Complemented with relevant Declaration of Performance

→ **Certified for burglary resistance**
Classification of Parameters MLTB-RC-5110-2024

DOOR MANUFACTURED TO CUSTOMER ORDER

STANDARD

- door leaf constructed of 2 steel skins 0.75 mm, edge rebated 18 x 18 mm total thickness 65 mm; reinforced for door closer application on both sides
- corner type door frame of steel 1.5 mm; fitted with perimeter rubber gasket and intumescent fire gasket
- door leaf inlet composed of rockwool and an intermediate layer of two fire protective boards ; weight of door 45 kg/m^2
- finish: PPC, palette RAL (258 colours, except signal ones)
- 2 pcs of hinges, regulated 3D, stainless steel (special version RC3)
- multi-point lock, PZ 92 mm, backset 65 mm
- reinforced stainless steel lever handle-handle set U-form on long shield; tested against burglary
- PZ cylinder, class 6C according to EN 1303, 6 keys
- 2 pcs of safety pins (in case of 3 hinges – 1 pc of safety pin)
- flush bolt in astragal of passive leaf (double leaf door)
- temporary-affixed steel bar threshold – for transportation only

ALTERNATIVE EQUIPMENT

- door frame: block, embracing or other type

ADDITIONAL EQUIPMENT

- multipoint lock: panic locks, motor lock or others
- ironmongery: knobs, panic bars
- electric strike plates, magnet locks, magnet contacts
- glass vision panel, rectangular
- smoke resistant gasket (S_{a4}, S_{200})
- automatic dropping gasket
- rain drip cap on door frame and/or on lower part of door leaf
- door closers
- alternative equipment and other door features on request

TECHNICAL PARAMETERS

- feature RC3 according to EN 1627
- basic features
  - mechanical resistance: class 3 (optional up to 4) according to standard EN 1192
  - mechanical durability: class 5 according to standard EN 16034 (200 000 cycles)
  - corrosion class: C3 (optional C5) according to standard EN ISO 12944
- optional: other classifications
- other functional features – according to relevant Declaration of Performance

STEEL CORNER FRAME

→ front view and cross section



range of equipment and necessary wall treatment (cut-outs) **are shown on separate data sheets**



→ detail C



→ detail D



→ **calculation of wall opening versus clear opening for the corner door frames:**



→ sizes of corner steel door frame

NOTE! door frame and installation gap to be duly filled, in accordance with certificate

→ **heat transfer coefficient Ud [W/m²K]**

corner frame	**without** thermal break	1,3

- automatic dropping gasket obligatory
- ventilation grill non applicable for antiburglary doors
- U value not calculated for doors equipped with glass vision panel

→ **acoustic insulation coefficient - on request (acoustic inlet)**

acoustic insulation Rw (C; Ctr)	
door without glass vision panel	42 (-1; -4)
door with glass vision panel	n.p.d.

- automatic dropping gasket obligatory for acoustic doors
- ventilation grill non applicable for antiburglary doors
- glazing type and dimensions according to the relevant DoP

STEEL CORNER FRAME

→ front view and cross section



range of equipment and necessary wall treatment (cut-outs) **are shown on separate data sheets**



→ detail C



→ detail D



→ **calculation of wall opening versus clear opening for the corner door frames:**



→ sizes of corner steel door frame

NOTE! door frame and installation gap to be duly filled, in accordance with certificate

→ **heat transfer coefficient Ud [W/m²K]**

corner frame	**without** thermal break	1,6

- automatic dropping gasket obligatory
- ventilation grill non applicable for antiburglary doors
- U value not calculated for doors equipped with glass vision panel

→ **acoustic insulation coefficient - on request (acoustic inlet)**

acoustic insulation Rw (C; Ctr)	
door without glass vision panel	42 (-1; -4)
door with glass vision panel	n.p.d.

- automatic dropping gasket obligatory for acoustic doors
- ventilation grill non applicable for antiburglary doors
- glazing type and dimensions according to the relevant DoP

STEEL BLOCK FRAME

→ front view and cross section



range of equipment and necessary wall treatment (cut-outs) **are shown on separate data sheets**



→ detail C



→ detail D



→ **calculation of wall opening versus clear opening for the block frames:**



→ sizes of block steel door frame

NOTE! door frame and installation gap to be duly filled, in accordance with certificate

→ **heat transfer coefficient Ud [W/m²K]**

block frame	**without** thermal break	1,6

- automatic dropping gasket obligatory
- ventilation grill non applicable for antiburglary doors
- U value not calculated for doors equipped with glass vision panel

→ **acoustic insulation coefficient - on request (acoustic inlet)**

acoustic insulation Rw (C; Ctr)	
door without glass vision panel	42 (-1; -4)
door with glass vision panel	n.p.d.

- automatic dropping gasket obligatory for acoustic doors
- ventilation grill non applicable for antiburglary doors
- glazing type and dimensions according to the relevant DoP

STEEL BLOCK FRAME

→ front view and cross section



range of equipment and necessary wall treatment (cut-outs) **are shown on separate data sheets**



→ detail C



→ detail D



→ **calculation of wall opening versus clear opening for the block frames:**



→ sizes of block steel door frame

NOTE! door frame and installation gap to be duly filled, in accordance with certificate

→ **heat transfer coefficient Ud [W/m²K]**

block frame	**without** thermal break	1,8

- automatic dropping gasket obligatory
- ventilation grill non applicable for antiburglary doors
- U value not calculated for doors equipped with glass vision panel

→ **acoustic insulation coefficient - on request (acoustic inlet)**

acoustic insulation Rw (C; Ctr)	
door without glass vision panel	42 (-1; -4)
door with glass vision panel	n.p.d.

- automatic dropping gasket obligatory for acoustic doors
- ventilation grill non applicable for antiburglary doors
- glazing type and dimensions according to the relevant DoP

STEEL EMBRACING FRAME

→ front view and cross section



range of equipment and necessary wall treatment (cut-outs) **are shown on separate data sheets**



→ detail C



→ detail D



→ **calculation of wall opening versus clear opening for the embracing door frames:**



→ sizes of embracing steel door frame

NOTE! door frame and installation gap to be duly filled, in accordance with certificate

→ **heat transfer coefficient Ud [W/m²K]**

wall embracing frame	**without** thermal break	1,3

- automatic dropping gasket obligatory
- ventilation grill non applicable for antiburglary doors
- U value not calculated for doors equipped with glass vision panel

→ **acoustic insulation coefficient - on request (acoustic inlet)**

acoustic insulation Rw (C; Ctr)	
door without glass vision panel	42 (-1; -4)
door with glass vision panel	n.p.d.

- automatic dropping gasket obligatory for acoustic doors
- ventilation grill non applicable for antiburglary doors
- glazing type and dimensions according to the relevant DoP

STEEL EMBRACING FRAME

→ front view and cross section



range of equipment and necessary wall treatment (cut-outs) **are shown on separate data sheets**



→ detail C



→ detail D



→ **calculation of wall opening versus clear opening for the embracing door frames:**



→ sizes of embracing steel door frame

NOTE! door frame and installation gap to be duly filled, in accordance with certificate

→ **heat transfer coefficient Ud [W/m²K]**

wall embracing frame	**without** thermal break	1,6

- automatic dropping gasket obligatory
- ventilation grill non applicable for antiburglary doors
- U value not calculated for doors equipped with glass vision panel

→ **acoustic insulation coefficient - on request (acoustic inlet)**

acoustic insulation Rw (C; Ctr)	
door without glass vision panel	42 (-1; -4)
door with glass vision panel	n.p.d.

- automatic dropping gasket obligatory for acoustic doors
- ventilation grill non applicable for antiburglary doors
- glazing type and dimensions according to the relevant DoP

HYBRID FRAME (60N)

→ front view and cross section



range of equipment and necessary wall treatment (cut-outs) **are shown on separate data sheets**



→ detail C



→ detail D



→ **calculation of wall opening versus clear opening for the hybrid door frames:**



→ hybrid steel frame

NOTE! door frame and installation gap to be duly filled, in accordance with certificate

→ **heat transfer coefficient Ud [W/m²K]**

hybrid frame	**without** thermal break	1,3

- automatic dropping gasket obligatory
- ventilation grill non applicable for antiburglary doors
- U value not calculated for doors equipped with glass vision panel

→ **acoustic insulation coefficient - on request (acoustic inlet)**

acoustic insulation Rw (C; Ctr)	
door without glass vision panel	42 (-1; -4)
door with glass vision panel	n.p.d.

- automatic dropping gasket obligatory for acoustic doors
- ventilation grill non applicable for antiburglary doors
- glazing type and dimensions according to the relevant DoP

DFM DOORS

HYBRID FRAME (60N)

→ front view and cross section



range of equipment and necessary wall treatment (cut-outs) **are shown on separate data sheets**



→ detail C



→ detail D



→ **calculation of wall opening versus clear opening for the hybrid door frames:**



→ hybrid steel frame

NOTE! door frame and installation gap to be duly filled, in accordance with certificate

→ **heat transfer coefficient Ud [W/m²K]**

hybrid frame	**without** thermal break	1,6

- automatic dropping gasket obligatory
- ventilation grill non applicable for antiburglary doors
- U value not calculated for doors equipped with glass vision panel

→ **acoustic insulation coefficient - on request (acoustic inlet)**

acoustic insulation Rw (C; Ctr)	
door without glass vision panel	42 (-1; -4)
door with glass vision panel	n.p.d.

- automatic dropping gasket obligatory for acoustic doors
- ventilation grill non applicable for antiburglary doors
- glazing type and dimensions according to the relevant DoP